

How to use the same Magento copy with multiple DBs and configurations

Article Updates

Updated Magento patch to allow Cache Refresh — [Unirgy](#) 2010/02/08 05:14

Procedure

Prepare original Magento copy for fast deployment of new copies

- Unpack Magento into /magento-1.3.2.4
- Apply [this patch](#), attached below
- Install ALL extensions and themes that will be used in ALL copies, using PEAR or direct file copy
 - (Optional) Proceed with configuration of Magento in this copy, if required for extension installations.
- Symlink /magento-1.3.2.4 to /magento-latest for easier future upgrades
- Create /magento-skel with the following structure:

```
/magento-skel/.htaccess - copy from /magento-latest/.htaccess  
/magento-skel/index.php - copy from /magento-latest/index.php and follow  
instructions below  
/magento-skel/js - symlink to /magento-latest/js (absolute path)  
/magento-skel/skin - symlink to /magento-latest/skin (absolute path)  
/magento-skel/etc - contains default configuration for new copies, copy from  
/magento-latest/app/etc  
/magento-skel/etc/modules - contains all modules' manifests, for later  
selective disabling for each copy  
/magento-skel/media - will contain media files, specific for each new copy  
/magento-skel/var - will contain temporary files, specific for each new copy
```

Update /magento-skel/index.php

- Make sure that \$mageFilename points to absolute path of /magento-latest/app/Mage.php
- Replace Mage::run() with:

```
$dir = dirname(__FILE__);  
Mage::run('', 'store', array(  
    'etc_dir'      => $dir . '/etc',  
    'media_dir'    => $dir . '/media',  
    'upload_dir'   => $dir . '/media/upload',  
    'var_dir'       => $dir . '/var',  
    'tmp_dir'       => $dir . '/var/tmp',  
    'cache_dir'     => $dir . '/var/cache',
```

```
'log_dir'      => $dir.'/var/log',
'session_dir'  => $dir.'/var/session',
'export_dir'   => $dir.'/var/export',
));
```

Create a new copy of skeleton template

- Copy /magento-skel to /copy1
- Update /copy1/etc/local.xml to reflect this copy's DB settings
 - (Optional) Create a new DB for this copy
 - If you do not have local.xml, proceed with Magento installation wizard
- Enable/disable relevant modules in /copy1/etc/modules
- Navigate to this copy's URL and wait for completion of DB install/upgrade

Conclusion

Now you have 1 copy of Magento core files, for unlimited number of installations and DBs, each with its own DB, configuration, enabled extensions, sessions, temporary and media files.

Upgrade of Magento or extensions needs to be done only once.

Applications

- Development: QA copies with different configuration/databases
- Running multiple stores with ease of maintenance

Configurable Dirs Patch for Magento 1.3.2.4

Click on file name to download as file:

[samecopy.patch](#)

```
diff -ruppbB magento/app/code/core/Mage/Core/Model/Config/Options.php
magento-1.3.2.4/app/code/core/Mage/Core/Model/Config/Options.php
--- magento/app/code/core/Mage/Core/Model/Config/Options.php
2009-09-23 14:52:55.000000000 -0400
+++ magento-1.3.2.4/app/code/core/Mage/Core/Model/Config/Options.php
2010-01-18 19:55:02.000000000 -0500
@@ -68,7 +68,7 @@ class Mage_Core_Model_Config_Options ext

    public function getDir($type)
    {
-        $this->_construct();
+        #$this->_construct();
        $method = 'get'.ucwords($type).'Dir';
    }
```

```

        $dir = $this->$method();
        if (! $dir) {
diff -ruppb magento/app/code/core/Mage/Core/Model/Config.php
magento-1.3.2.4/app/code/core/Mage/Core/Model/Config.php
--- magento/app/code/core/Mage/Core/Model/Config.php 2009-09-23
14:52:57.000000000 -0400
+++ magento-1.3.2.4/app/code/core/Mage/Core/Model/Config.php
2009-11-15 22:54:56.000000000 -0500
@@ -213,7 +213,7 @@ class Mage_Core_Model_Config extends Mag

        $localConfigLoaded = $this->loadFile($etcDir.DS.'local.xml');

-
+    if (Mage::isInstalled()) {
+        if (Mage::isInstalled($options)) {
            if ($this->_canUseCacheForInit()) {
Varien_Profiler::start('mage::app::init::config::load_cache');
            $loaded = $this->loadCache();
@@ -286,6 +286,9 @@ class Mage_Core_Model_Config extends Mag
{
        $this->_allowCacheForInit = false;
        $this->_useCache = false;
+
+        if (!$options) {
+            $options = Mage::registry('user_options');
+
        }
        return $this->init($options);
    }

diff -ruppb magento/app/code/core/Mage/Install/etc/install.xml
magento-1.3.2.4/app/code/core/Mage/Install/etc/install.xml
--- magento/app/code/core/Mage/Install/etc/install.xml 2009-09-23
14:51:54.000000000 -0400
+++ magento-1.3.2.4/app/code/core/Mage/Install/etc/install.xml
2009-11-15 22:31:06.000000000 -0500
@@ -62,16 +62,19 @@
                <path>/app/etc</path>
                <existence>1</existence>
                <recursive>0</recursive>
+
                <option_dir>etc</option_dir>
            </app/etc>
            <var>
                <path>/var</path>
                <existence>1</existence>
                <recursive>1</recursive>
+
                <option_dir>var</option_dir>
            </var>
            <media>
                <path>/media</path>
                <existence>1</existence>
                <recursive>1</recursive>
+
                <option_dir>media</option_dir>
            </media>

```

```

                </writeable>
            </filesystem>
diff -ruppbB
magento/app/code/core/Mage/Install/Model/Installer/Filesystem.php
magento-1.3.2.4/app/code/core/Mage/Install/Model/Installer/Filesystem.p
hp
--- magento/app/code/core/Mage/Install/Model/Installer/Filesystem.php
2009-09-23 14:51:54.000000000 -0400
+++
magento-1.3.2.4/app/code/core/Mage/Install/Model/Installer/Filesystem.p
hp 2009-11-15 22:51:44.000000000 -0500
@@ -66,7 +66,8 @@ class Mage_Install_Model_Installer_Files
        foreach ($config['writeable'] as $item) {
            $recursive = isset($item['recursive']) ?
$item['recursive'] : false;
            $existence = isset($item['existence']) ?
$item['existence'] : false;
-           $checkRes = $this->_checkPath($item['path'],
$recursive, $existence, 'write');
+           $path = isset($item['option_dir']) ?
Mage::getConfig()->getOptions()->getDir($item['option_dir']) :
$item['path'];
+           $checkRes = $this->_checkPath($path, $recursive,
$existence, 'write');
            $res = $res && $checkRes;
        }
    }
@@ -85,7 +86,11 @@ class Mage_Install_Model_Installer_Files
    protected function _checkPath($path, $recursive, $existence,
$mode)
    {
        $res = true;
+       if ($path[0]=='/' || $path[0]=='\\' || $path[1]==':') {
+           $fullPath = $path;
+       } else {
+           $fullPath = dirname(Mage::getRoot()).$path;
+       }
        if ($mode == self::MODE_WRITE) {
            $setError = false;
            if ($existence) {
diff -ruppbB magento/app/Mage.php magento-1.3.2.4/app/Mage.php
--- magento/app/Mage.php 2009-09-23 14:53:39.000000000 -0400
+++ magento-1.3.2.4/app/Mage.php 2010-01-18 19:55:28.000000000 -0500
@@ -452,6 +452,8 @@ final class Mage {
        Varien_Profiler::start('mage');

        Varien_Profiler::start('mage::app');
+
+       self::register('user_options', is_string($options) ?
array('etc_dir'=>$options) : (array)$options);
        self::app($code, $type, $options);

```

```
        Varien_Profiler::stop('mage::app');

@@ -518,10 +518,13 @@ final class Mage {
    if (!empty($options['etc_dir'])) {
        $etcDir = $options['etc_dir'];
    }
+   if ($etcDir[0]=='/' || $etcDir[0]=='\\' ||
$etcDir[1]==':') {
+       $localConfigFile = $etcDir . DS . 'local.xml';
+   } else {
        $localConfigFile = self::getRoot() . DS . $etcDir . DS .
'local.xml';
+   }

    $isInstalled = false;
-
    if (is_readable($localConfigFile)) {
        $localConfig = simplexml_load_file($localConfigFile);
        date_default_timezone_set('UTC');
```

From:

<https://unirgy.com/wiki/> - **UnirgyWiki**



Permanent link:

<https://unirgy.com/wiki/magento/same-copy-multiple-dbs>

Last update: **2010/02/08 10:15**