2020/08/27 10:52 1/4 uRapidFlow Customization

# uRapidFlow Customization

### **Events**

A general way to add observers to the events is:

 Declare an observer in your custom module configuration, app/etc/local.xml or app/etc/modules/\* (any new file)

An example: app/etc/modules/MyCustom Module.xml

MyCustom Module.xml

```
<?xml version="1.0"?>
<config>
  <qlobal>
    <events>
      <urapidflow_product_import_after_fetch>
        <observers>
          <mycustommodule>
            <type>singleton</type>
            <class>MyCustom Module Model Observer</class>
            <method>urapidflow product import after fetch</method>
          </mycustommodule>
        </observers>
      </urapidflow_product_import_after_fetch>
    </events>
  </global>
</config>
```

app/code/local/MyCustom/Module/Model/Observer.php

### Observer.php

```
<?php

class MyCustom_Module_Model_Observer
{
    public function urapidflow_product_import_after_fetch($observer)
    {
        $vars = $observer->getEvent()->getVars();
        $oldData = $vars['old_data'];

        // custom logic here
    }
}
```

### Last update: 2010/10/14 19:27

### **Product Import Events**

There are 5 stages during product import process where a custom logic can be plugged in as an event observer:

- urapidflow\_product\_import\_after\_fetch after fetching new and old data
- urapidflow\_product\_import\_after\_validate after validating the new data
- urapidflow\_product\_import\_after\_diff after finding the difference between new and old data
- urapidflow product import after save after all changes has been saved
- urapidflow\_product\_import\_after\_rtidx after real-time reindex ran (if enabled in profile)

The events are fired for each page of data (by default 100 rows), and each stage has more vars available than previous, and including all vars that were available before.

### urapidflow product import after fetch

#### Vars

- profile instance of current Unirgy RapidFlow Model Profile
- new\_data rows fetched from CSV file (including any default values for missing columns, as specified in the profile)
- old data product information for matching SKUs fetched from DB
- skus mapping of SKUs in the current page to product IDs
- attr value ids EAV attribute value IDs for fetched old data

#### **Example**

This example observer will change weight values of "2kg" and "470g" into correct decimal weight value.

app/code/local/MyCustom/Module/Model/Observer.php

### Observer.php

https://unirgy.com/wiki/ Printed on 2020/08/27 10:52

2020/08/27 10:52 3/4 uRapidFlow Customization

### urapidflow product import after validate

#### **Vars**

valid - which products passed or not validation

### urapidflow product import after diff

#### **Vars**

- insert entity new products to be created
- change attr changed attributes
- change website changed product-website associations
- change stock changed inventory stock information
- change\_category\_product changed product-category associations

### **Product Export Events**

There are 2 stages during product import process where a custom logic can be plugged in as an event observer:

- urapidflow\_catalog\_product\_export\_before\_format after fetching data from db and before formating for output
- urapidflow\_catalog\_product\_export\_before\_output after formating for output and right before writing to file

The events are fired for each page of data (by default 100 rows), and each stage has more vars available than previous, and including all vars that were available before.

### urapidflow\_catalog\_product\_export\_before\_format

### Vars

- profile
- products
- fields

## Last update: 2010/10/14 19:27

### urapidflow\_catalog\_product\_export\_before\_output

### Vars

- profile
- products
- fields
- rows

From:

https://unirgy.com/wiki/ - UnirgyWiki

Permanent link:

https://unirgy.com/wiki/urapidflow/customization

Last update: 2010/10/14 19:27



https://unirgy.com/wiki/ Printed on 2020/08/27 10:52